

## 92 Series - 6 Function IP Wide Band Transmitter

### TRANSMITTER PART NUMBER

92 2 06TX      6 Function

IP Wide Band Transmitter



### SYSTEM CONTENTS

1 x IP Transmitter

### IP TRANSMITTER SPECIFICATION

<b>SWITCH - Type</b>	Tactile Dome on PCB Keypad	
<b>Battery - Type</b>	4 x AAA Alkaline Manganese in holder (6 Volts)	
<b>INDICATOR</b>		
Type	1 x Red LED	
Off	Transmitter OFF (The STOP Button has been pressed and released)	
Slow flash	Transmitter ON and ready for use (The SET Button has been pressed and released)	
On	Transmitting (A STOP, SET or Function Button is being pressed)	
Fast flash	Transmitting – Indication that the battery will need replacing soon	
<b>Current Drawn</b>		
Quiescent	15 micro amps	
Operating	25 milliamps	
<b>PROTECTION</b>		
Reverse polarity	Protected	
IP Rating	67	
Conformal coating	No	
Registration codes	Over 16 million	
<b>PERFORMANCE</b>		
Temp Range	-10°C to + 40°C (13°F to + 104°F)	
Range Nominal as supplied	60 metres (200 ft) from the Receiver, when driving a momentary output without signal drop out	
Transmitted power	1mW Typical	
<b>COMPLIANCE</b>		
EMC	2004/104/EEC	Exceeds ETSI 300 220
Modulation	FM	
Frequencies	418 MHz F1D	USA (optional UK)
	433.92 MHz F1D	World wide (optional USA)