

92 Series - 20 Function IP Wide Band Transmitter

TRANSMITTER PART NUMBER

92 2 20TX

20 Function

IP Wide Band Transmitter



<u>SYSTEM CONTENTS</u>	
1 x IP Transmitter	

IP TRANSMITTER SPECIFICATION

SWITCH - Type	Tactile Dome on PCB Keypad	
Battery - Type	4 x AAA Alkaline Manganese in holder (6 Volts)	
INDICATOR	1 x Red LED	
Type	Transmitter OFF (The STOP Button has been pressed and released)	
Off	Transmitter ON and ready for use (The SET Button has been pressed and released)	
Slow flash	Transmitting (A STOP, SET or Function Button is being pressed)	
On	Transmitting – Indication that the battery will need replacing soon	
Fast flash		
Current Drawn	15 micro amps	
Quiescent	25 milliamps	
Operating		
PROTECTION	Protected	
Reverse polarity	67	
IP Rating	No	
Conformal coating	Over 16 million	
Registration codes		
PERFORMANCE	-10°C to + 40°C (13°F to + 104°F)	
Temp Range	60 metres (200 ft) from the Receiver, when driving a momentary output without signal drop out	
Range Nominal as supplied	1mW Typical	
Transmitted power		
COMPLIANCE	2004/104/EEC Exceeds ETSI 300 220	
EMC	FM	
Modulation	418 MHz F1D USA (optional UK)	
Frequencies	433.92 MHz F1D World wide (optional USA)	