

93 Series - 4 Function IP Narrow Band Transmitter

TRANSMITTER PART NUMBER

93 2 04TX

4 Function

IP Narrow Band Transmitter



SYSTEM CONTENTS

1 x IP Transmitter

IP TRANSMITTER SPECIFICATION

| | |
|---------------------------|---|
| SWITCH - Type | Tactile Dome on PCB Keypad |
| Battery - Type | 4 x AAA Alkaline Manganese in holder (6 Volts) |
| INDICATOR | |
| Type | 1 x Red LED |
| Off | Transmitter OFF (The STOP Button has been pressed and released) |
| Slow flash | Transmitter ON and ready for use (The SET Button has been pressed and released) |
| On | Transmitting (A STOP, SET or Function Button is being pressed) |
| Fast flash | Transmitting – Indication that the battery will need replacing soon |
| Current Drawn | |
| Quiescent | 15 micro amps |
| Operating | 25 milliamps |
| PROTECTION | |
| Reverse polarity | Protected |
| IP Rating | 67 |
| Conformal coating | No |
| Registration codes | Over 16 million |
| PERFORMANCE | |
| Temp Range | -10° C to + 40° C (13° F to + 104° F) |
| Range Nominal as supplied | 60 metres (200 ft) from the Receiver, when driving a momentary output without signal drop out |
| Transmitted power | 10mW Typical |
| COMPLIANCE | |
| EMC | 2004/104/EEC Exceeds ETSI 300 220 |
| Modulation | FM |
| Frequencies | 434 MHz Band, 15 Frequencies |