

# 93 Series - 6 Function IP Narrow Band Transmitter

## TRANSMITTER PART NUMBER

93 2 06TX      6 Function

IP Narrow Band Transmitter



## SYSTEM CONTENTS

1 x IP Transmitter

## IP TRANSMITTER SPECIFICATION

|                           |   |                      |
|---------------------------|---|----------------------|
| <b>SWITCH - Type</b>      | Tactile Dome on PCB Keypad  |                      |
| <b>Battery - Type</b>     | 4 x AAA Alkaline Manganese in holder (6 Volts)  |                      |
| <b>INDICATOR</b>          | 1 x Red LED   |                      |
| Type                      | Transmitter OFF (The STOP Button has been pressed and released)                               |                      |
| Off                       | Transmitter ON and ready for use (The SET Button has been pressed and released)               |                      |
| Slow flash                | Transmitting (A STOP, SET or Function Button is being pressed)                                |                      |
| On                        | Transmitting – Indication that the battery will need replacing soon                           |                      |
| Fast flash                |   |                      |
| <b>Current Drawn</b>      |   |                      |
| Quiescent                 | 15 micro amps   |                      |
| Operating                 | 25 milliamps  |                      |
| <b>PROTECTION</b>         |   |                      |
| Reverse polarity          | Protected   |                      |
| IP Rating                 | 67  |                      |
| Conformal coating         | No  |                      |
| Registration codes        | Over 16 million   |                      |
| <b>PERFORMANCE</b>        |   |                      |
| Temp Range                | -10° C to + 40° C (13° F to + 104° F)   |                      |
| Range Nominal as supplied | 60 metres (200 ft) from the Receiver, when driving a momentary output without signal drop out |                      |
| Transmitted power         | 10mW Typical  |                      |
| <b>COMPLIANCE</b>         |   |                      |
| EMC                       | 2004/104/EEC  | Exceeds ETSI 300 220 |
| Modulation                | FM  |                      |
| Frequencies               | 434 MHz Band, 15 Frequencies  |                      |