

93 Series - 28 Function IP Narrow Band Transmitter with Shift Function

TRANSMITTER PART NUMBER

93 3 28TX 28 Function

IP Narrow Band Transmitter with Shift Buttons



SYSTEM CONTENTS

1 x IP Transmitter

IP TRANSMITTER SPECIFICATION

SWITCH - Type	Tactile Dome on PCB Keypad
Battery - Type	4 x AAA Alkaline Manganese in holder (6 Volts)
INDICATOR	
Type	1 x Red LED
Off	Transmitter OFF (The STOP Button has been pressed and released)
Slow flash	Transmitter ON and ready for use (The SET Button has been pressed and released)
On	Transmitting (A STOP, SET or Function Button is being pressed)
Fast flash	Transmitting – Indication that the battery will need replacing soon
Current Drawn	
Quiescent	15 micro amps
Operating	25 milliamps
PROTECTION	
Reverse polarity	Protected
IP Rating	67
Conformal coating	No
Registration codes	Over 16 million
PERFORMANCE	
Temp Range	-10° C to + 40° C (13° F to + 104° F)
Range Nominal as supplied	60 metres (200 ft) from the Receiver, when driving a momentary output without signal drop out
Transmitted power	10mW Typical
COMPLIANCE	
EMC	2004/104/EEC Exceeds ETSI 300 220
Modulation	FM
Frequencies	434 MHz Band, 15 Frequencies